





SECURE DOORS
FOR STORING
**CONFIDENTIAL
DOCUMENTS AND
LIMITED AMOUNT OF
CASH AND VALUABLES**



SECURITY BOOKROOM DOOR



BURGLARY RESISTANT PROTECTION

KEY FEATURES

- Overall Door thickness of:
 - 136mm for Class A Door
 - 132mm for Class B Door
- The protective layer consists of a steel door plate of:
 - 12mm for Class A Door
 - 9mm for Class B Door
- Secured by 4 active front bolts with diameter of 32mm and full height fixed rear docking bolt.
- Both Doors are secured by a Sargent & Greenleaf certified three-wheel combination lock and a 8-lever double bitted Key Lock as standard. Both locks operate independently.
- The Keyless Combination Lock and KeyLock are protected by 2 relocers. Any forced attempt to dislodge the locks would activate relocker and restricts the movement of the internal boltwork system.
- The relocker is further protected by drill resistant hard plates.
- The door comes standard with a painted grey primer based finish.

SECURITY BOOKROOM DOOR

PRODUCT SPECIFICATIONS

Model	External Dimensions (mm)	Clear Opening (mm)	Wall Opening (mm)	Wall Thickness (mm)	Approx. Net Weight (kg)
Class A	2005(H) x 1187(W)	1892(H) x 900(W)	1962(H) x 1090(W)	200 (inclusive of plastering)	350 (Door) and 25 (Gate)
Class B	2005(H) x 1187(W)	1892(H) x 900(W)	1962(H) x 1090(W)	200 (inclusive of plastering)	305 (Door) and 25 (Gate)

STANDARD LOCKS



KEYLESS COMBINATION LOCK

Secured by a certified 3-wheel Keyless Combination Lock capable of 1,000,000 changes of code. The operation of this lock is simple. The code can be changed easily and security can be maintained over the safe whenever there is a change of staff.

KEYLOCK

The door is secured by certified a 8-lever double bitted key lock.

OPTIONS



LOCKS


- Various high-security electronic locks
- Two or three movement Time Lock may be fitted as an additional requirement



DAY GATE

An Optional Day Gate can be fitted to the door for ventilation during the day or as control when the door is open. The Day Gate is secured by two high security Mortice Deadlocks.

"WRAP AROUND WALL" FRAME



Door frame is fabricated from steel sections, bent to form a single structure. Vestibule side frames at full height of the door are attached to the frame and grip the inside of wall.

This design provides stronger resistance against attacks to the door.

WHEN ORDERING, PLEASE STATE:

- Wall thickness
- Type of wall e.g. brick, R.C etc.
- Hung of door required
- If to be installed in multi-storey building, state floor level
- Path of access to where door is to be installed.

NOTE

Chubb safes Doors are designed primarily against physical attack. For recommended storage of paper documents and computer media, ask for details of Chubb safes Fire Resistant Cabinets or Chubb safes Data Cabinets.

Authorised dealer

www.chubbsafes.com